NSN 5935-01-231-8262

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-231-8262

Body Style:
Straight shape
Overall Length:
2.880 inches
Overall Height:
1.000 inches
Overall Width:
0.739 inches
Environmental Protection:
Moisture resistant and shock resistant and vibration resistant and corrosion resistant
Unthreaded Mounting Hole Diameter:
0.215 inches
Distance Between Mounting Facility Centers:
2.531 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
50 single mating end
Contact Removability:
Removable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
5.0 single mating end single contact grouping
Polarization Method:
Mating end
Shell Type:
Solid
Connector Locking Method:
Friction
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and silver single mating end single contact grouping
Insert Material:
Glass single mating end and plastic diallyl phthalate single mating end
Terminal Type:
Crimp single mating end single contact grouping
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Cadmium

NSN 5935-01-231-8262

Electrical Receptacle Connector - Page 2 of 2



Shell Surface Treatment Specification:

Qq-p-416, type 2, class 3 federal specification single treatment response

Insert Material Specification:

Mil-p-19833, ty gdi-30f military specification all material responses single mating end

Included Contact Quantity:

50 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold and contact surfaces silver

Precious Material And Weight:

0.050 gold grains, troy and 0.050 silver grains, troy

Precious Material:

Gold and silver

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-p-19833 spec.