

View Online at <https://aerobasegroup.com/nsn/5935-01-232-0985>

Thread Class:

2a and 2a and 2a

Thread Direction:

Right-hand and right-hand and right-hand

Body Style:

Straight shape, external coupling

Overall Length:

1.394 inches

Overall Diameter:

1.376 inches

Environmental Protection:

Moisture proof and salt water resistant and vibration proof and shock resistant and cold resistant and heat resistant and explosion proof

Distance From Mounting Shoulder To Front Face:

0.869 inches

Mounting Facility Thickness:

0.199 inches

Threaded Device Type:

Back shell and coupling facility and mounting bushing

Mating End Quantity:

1

Contact Position Arrangement Style:

16s-1 single mating end

Contact Removability:

Removable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

22.0 single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

500.0 single mating end single contact grouping

Contact Maximum Dc Voltage Rating In Volts:

700.0 single mating end single contact grouping

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

0.0

Shell Type:

Solid

Connector Locking Method:

Externally threaded shell

Operating Temperature Rating:

Between -55.0 degrees celsius and 125.0 degrees celsius

Features Provided:

Safety wire hole

Thready Qty Per Inch (tpi):

20 and 20 and 20

Thread Size:

0.875 inches and 1.000 inches and 1.000 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and nickel single mating end single contact grouping

Insert Material:

Rubber single mating end

Contact Surface Treatment Specification:

Mil-g-45204, type 2, grade c, class 1 military specification 1st treatment response single mating end single contact grouping and qq-n-290, class 2 federal specification 2nd treatment response single mating end single contact grouping

Terminal Type:

Crimp single mating end single contact grouping

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Cadmium and chromate

Shell Surface Treatment Specification:

Qq-p-416, type 2, cl 3 federal specification all treatment responses

Included Contact Quantity:

7 single mating end single contact grouping

Bushing Accommodation Hole Shape:

Round

Included Contact Type:

Round socket single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.007 gold grains, troy

Precious Material:

Gold

Thread Series Designator:

Unef and unef and unef

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.