Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-232-1515

**Thread Class:** 

2a and 2b

**Thread Direction:** 

Right-hand

Body Style:

Straight shape

**Overall Length:** 

1.850 inches

**Overall Height:** 

0.460 inches

Overall Width:

0.250 inches

**Threaded Device Type:** 

Coupling facility

Mating End Quantity:

1

**Contact Position Arrangement Style:** 

2 rows of contacts non-inserted board single mating end

## Contact Removability:

Nonremovable single mating end single contact grouping

## **Contact Maximum Current Rating In Amps:**

5.0 single mating end single contact grouping

**Polarization Method:** 

Jackscrew

**Connector Locking Method:** 

Jackscrew-socket

Thready Qty Per Inch (tpi):

56

## Thread Size:

0.086 inches

#### **Terminal Location:**

Back single mating end single contact grouping

#### **Contact Material:**

Copper alloy single mating end single contact grouping

#### **Contact Surface Treatment:**

Gold single mating end single contact grouping

## **Insert Material:**

Plastic polyphenylene single mating end

## **Contact Surface Treatment Specification:**

Mil-g-45204 military specification single treatment response single mating end single contact grouping

## **Terminal Type:**

Solder well single mating end single contact grouping

# NSN 5935-01-232-1515

Electrical Plug Connector - Page 2 of 2



**Contact Material Specification:** Qq-c-530 federal specification single material response single mating end single contact grouping **Insert Material Specification:** Mil-m-24519 military specification single material response single mating end **Included Contact Quantity:** 30 single mating end single contact grouping **Included Contact Type:** Round pin single mating end single contact grouping **Precious Material And Location:** Contact surfaces gold **Precious Material And Weight:** 0.030 gold grains, troy **Precious Material:** Gold **Thread Series Designator:** Unc Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A039b0

Mil-std (military Standard):

Mil-g-45204 spec.