

View Online at <https://aerobasegroup.com/nsn/5935-01-232-1520>

**Body Style:**

Right angle type

**Overall Length:**

2.800 inches

**Overall Height:**

1.065 inches

**Overall Width:**

0.465 inches

**Environmental Protection:**

Cold resistant and heat resistant

**Unthreaded Mounting Hole Diameter:**

0.096 inches

**Distance Between Mounting Facility Centers:**

1.660 inches

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

2 rows of contacts non-inserted board single mating end

**Contact Removability:**

Nonremovable single mating end single contact grouping

**Connector Locking Method:**

Latch

**End Application:**

Countermeasures set, an/alm233 se

**Terminal Location:**

Side single mating end single contact grouping

**Contact Material:**

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping and nickel single mating end single contact grouping

**Insert Material:**

Plastic polyester single mating end and glass fiber single mating end

**Contact Surface Treatment Specification:**

Mil-g-45204, type 1, gr c military specification 1st treatment response single mating end single contact grouping and qq-n-290, cl 2 federal specification 2nd treatment response single mating end single contact grouping

**Terminal Type:**

Pin single mating end single contact grouping

**Contact Material Specification:**

Astm-b-159, 3/4 hard assn standard single material response single mating end single contact grouping

**Insert Material Specification:**

Mil-m-24519, ty gpt-30f military specification all material responses single mating end

**Included Contact Quantity:**

26 single mating end single contact grouping

**Included Contact Type:**

Flat pin single mating end single contact grouping

**Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:**

0.026 gold grains, troy

**Precious Material:**

Gold

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A039b0

**Mil-std (military Standard):**

Mil-g-45204 spec.