

View Online at <https://aerobasegroup.com/nsn/5935-01-232-4488>

Thread Class:

2a

Thread Direction:

Right-hand

Overall Length:

0.750 inches

Unthreaded Mounting Hole Diameter:

Between 0.100 inches and 0.105 inches

Distance From Mounting Shoulder To Front Face:

0.378 inches

Threaded Device Type:

Coupling facility

Mating End Quantity:

2

Contact Position Arrangement Style:

Sma 1st mating end

Contact Removability:

Nonremovable all mating ends single contact grouping

Contact Maximum Frequency Rating:

18000.0 megahertz all mating ends single contact grouping

Shell Type:

Solid

Connector Locking Method:

Externally threaded shell and friction

Thready Qty Per Inch (tpi):

36

Thread Size:

0.250 inches

Contact Material:

Metal all mating ends single contact grouping

Contact Surface Treatment:

Gold all mating ends single contact grouping

Contact Surface Treatment Specification:

Mil-g-45204 military specification single treatment response all mating ends single contact grouping

Shell Material:

Stainless steel

Shell Surface Treatment:

Passivate

Included Contact Quantity:

1 2nd mating end single contact grouping

Included Contact Type:

Coaxial socket all mating ends single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.010 gold grains, troy

Precious Material:

Gold

Thread Series Designator:

Uns

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.