# NSN 5935-01-232-5648

**Thread Class:** 

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-232-5648

2a and 2b
Thread Direction:
Right-hand
Body Style:
Straight type
Overall Length:
3.850 inches
Overall Height:
0.625 inches
Overall Width:
0.250 inches
Environmental Protection:
Shock resistant and vibration resistant and corrosion resistant and humidity resistant
Unthreaded Mounting Hole Diameter:
0.120 inches
Distance Between Mounting Facility Centers:
3.600 inches
Threaded Device Type:
Coupling facility
Mating End Quantity:
1
Contact Position Arrangement Style:
2 rows of contacts non-inserted board single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
5.0 single mating end single contact grouping
Polarization Method:
Jackscrew
Connector Locking Method:
Jackscrew-socket
Thready Qty Per Inch (tpi):
56
Thread Size:
0.086 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and copper single mating end single contact grouping and nickel single mating end single
contact grouping

# NSN 5935-01-232-5648

Electrical Receptacle Connector - Page 2 of 2



#### **Insert Material:**

Plastic diallyl phthalate single mating end and glass fiber single mating end

# **Contact Surface Treatment Specification:**

Mil-g-45204, type 2, grade c, class 1 military specification 1st treatment response single mating end single contact grouping and mil-c-14550 military specification 2nd treatment response single mating end single contact grouping and qq-n-290 class 2 federal specification 3rd treatment response single mating end single contact grouping

#### **Terminal Type:**

Pin single mating end single contact grouping

#### **Contact Material Specification:**

Mil-c-55302 military specification single material response single mating end single contact grouping

# **Included Contact Quantity:**

60 single mating end single contact grouping

#### **Included Contact Type:**

Round pin single mating end single contact grouping

#### **Precious Material And Location:**

Contact surfaces gold

# **Precious Material And Weight:**

0.060 gold grains, troy

**Precious Material:** 

Gold

# **Thread Series Designator:**

Unc

Shelf Life:

N/a

**Unit Of Measure:** 

Demilitarization:

No

Fiig:

A039b0

# Mil-std (military Standard):

Mil-c-55302 spec.