

View Online at <https://aerobasegroup.com/nsn/5935-01-232-6472>

Body Style:

Angle shape

Overall Length:

0.980 inches

Overall Height:

0.650 inches

Overall Width:

0.235 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

2 rows of contacts non-inserted board single mating end

Contact Removability:

Removable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

1.0 single mating end single contact grouping

Polarization Method:

Shell

Connector Locking Method:

Friction

Connector Cable Strain Relief Method:

Bracket

End Application:

Air traffic controller aircraft switching system an/fsc-92v

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and nickel single mating end single contact grouping

Insert Material:

Plastic polyester single mating end and glass single mating end

Contact Surface Treatment Specification:

Mil-g-45204 military specification 1st treatment response single mating end single contact grouping and qq-n-290 federal specification 2nd treatment response single mating end single contact grouping

Terminal Type:

Tab, solder lug single mating end single contact grouping

Contact Material Specification:

Qq-b-750, composition a federal specification single material response single mating end single contact grouping

Insert Material Specification:

Mil-m-24519, ty gpt-30f military specification all material responses single mating end

Included Contact Quantity:

16 single mating end single contact grouping

Included Contact Type:

Flat socket single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.016 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.