NSN 5935-01-232-6476

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-232-6476

Thread Class:
2a and 2b
Thread Direction:
Right-hand
Body Style:
Straight type
Overall Length:
3.250 inches
Overall Height:
0.565 inches
Overall Width:
0.350 inches
Environmental Protection:
Shock resistant and vibration resistant and corrosion resistant and humidity resistant
Unthreaded Mounting Hole Diameter:
0.120 inches
Threaded Device Type:
Coupling facility
Mating End Quantity:
1
Contact Removability:
Nonremovable single mating end single contact grouping
Polarization Method:
Jackscrew
Connector Locking Method:
Jackscrew-socket
Thready Qty Per Inch (tpi):
56
Thread Size:
0.086 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and nickel single mating end single contact grouping and copper single mating end single
contact grouping
Insert Material:
Glass fiber single mating end and plastic diallyl phthalate single mating end or plastic polyphenylene single mating end
Contact Surface Treatment Specification:
Mil-g-45204, type 2, grade c, cl 1 military specification 1st treatment response single mating end single contact grouping and qq-n-290, cl 2

federal specification 2nd treatment response single mating end single contact grouping and mil-c-14550 military specification 3rd treatment

Terminal Type:

Solder well single mating and single contact grouping

response single mating end single contact grouping

NSN 5935-01-232-6476

Electrical Receptacle Connector - Page 2 of 2



Contact Material Specification:

Qq-c-530 federal specification single material response single mating end single contact grouping or qq-b-750 federal specification single material response single mating end single contact grouping

Included Contact C	uantity
--------------------	---------

80 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.080 gold grains, troy

Precious Material:

Gold

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.