Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-232-6482

**Body Style:** Right angle type **Overall Length:** 0.700 inches **Body Height:** 0.125 inches **Environmental Protection:** Corrosion resistant and shock resistant and vibration resistant Mating End Quantity: 1 **Contact Position Arrangement Style:** 1 row of contacts non-inserted board single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 3.5 single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 250.0 single mating end single contact grouping **Connector Locking Method:** Friction **End Application:** 5820-01-162-3402 receiver-transmitter **Terminal Location:** Side single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping **Insert Material:** Plastic polyamide single mating end **Terminal Type:** Tab, solder lug single mating end single contact grouping **Included Contact Quantity:** 7 single mating end single contact grouping **Included Contact Type:** Flat pin single mating end single contact grouping **Precious Material And Location:** Contact surfaces gold **Precious Material And Weight:** 0.007 gold grains, troy **Precious Material:** Gold

Electrical Receptacle Connector - Page 2 of 2



Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A039b0