

View Online at <https://aerobasegroup.com/nsn/5935-01-232-9819>

Thread Direction:

Right-hand

Body Style:

Straight shape, external coupling

Overall Length:

34.16 millimeters

Overall Height:

Between 39.1 millimeters and 40.2 millimeters

Overall Width:

Between 39.1 millimeters and 40.2 millimeters

Unthreaded Mounting Hole Diameter:

Between 3.1 millimeters and 3.5 millimeters

Center To Center Distance Between Mounting Facilities Parallel To Height:

30.76 millimeters

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

30.76 millimeters

Distance From Mounting Shoulder To Front Face:

Between 19.2 millimeters and 20.8 millimeters

Threaded Device Type:

Back shell

Mating End Quantity:

1

Contact Position Arrangement Style:

21-11 single mating end

Contact Removability:

Removable single mating end single contact grouping

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

0.0

Shell Type:

Solid

Connector Locking Method:

Detent

Thread Size:

31.0 millimeters

Thread Pitch In Millimeters:

1.00

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Contact Surface Treatment Specification:

Mil-g-45204 military specification single treatment response single mating end single contact grouping

Terminal Type:

Crimp single mating end single contact grouping

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Nickel

Shell Surface Treatment Specification:

Mil-c-26074 military specification single treatment response

Thread Tolerance Class:

6g external

Included Contact Quantity:

11 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.011 gold grains, troy

Precious Material:

Gold

Test Data Document:

81349-doc-c-38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Iso m

Specification Data:

81349-doc-c-38999/40 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.