## NSN 5935-01-233-8167

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-233-8167

view Online at https://aerobasegroup.com/nsn/5935-01-233-6167
Body Style:
Right angle type
Overall Length:
1.040 inches
Overall Width:
0.520 inches
Body Height:
0.238 inches
Environmental Protection:
Corrosion resistant and humidity resistant and shock resistant and vibration resistant
Mating End Quantity:
1
Contact Position Arrangement Style:
2 rows of contacts non-inserted board single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
3.0 single mating end single contact grouping
Polarization Method:
Mating end
Connector Locking Method:
Friction
Terminal Location:
Side single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and nickel single mating end single contact grouping
Insert Material:
Plastic diallyl phthalate single mating end
Contact Surface Treatment Specification:
Mil-g-45204 military specification 1st treatment response single mating end single contact grouping and qq-n-290 federal specification 2nd
treatment response single mating end single contact grouping
Terminal Type:
Tab, solder lug single mating end single contact grouping
Contact Material Specification:
Qq-c-533 federal specification single material response single mating end single contact grouping
Included Contact Quantity:

Included Contact Type:

Flat socket single mating end single contact grouping

20 single mating end single contact grouping

**Precious Material And Location:** 

Contact surfaces gold

## NSN 5935-01-233-8167

Electrical Receptacle Connector - Page 2 of 2



<b>Precious Material And Weight:</b>
0.020 gold grains, troy
Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0

Mil-std (military Standard):

Mil-g-45204 spec.