## NSN 5935-01-233-8170

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-233-8170

Body Style:
Straight type
Overall Length:
1.000 inches
Overall Height:
0.800 inches
Overall Width:
0.220 inches
Environmental Protection:
Cold resistant and heat resistant and thermal shock resistant
Unthreaded Mounting Hole Diameter:
0.102 inches
Distance Between Mounting Facility Centers:
0.750 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
1 row of contacts non-inserted board single mating end
Contact Removability:
Nonremovable single mating end all contact groupings
Connector Locking Method:
Friction
Terminal Location:
Back single mating end all contact groupings
Contact Material:
Copper alloy single mating end all contact groupings
Contact Surface Treatment:
Gold single mating end all contact groupings and copper single mating end all contact groupings
Insert Material:
Plastic diallyl phthalate single mating end
Contact Surface Treatment Specification:
Mil-g-45204, ty ii, grade c, cl 4 military specification 1st treatment response single mating end all contact groupings and mil-c-14550, cl 4
military specification 2nd treatment response single mating end all contact groupings
Criticality Code Justification:
Feat
Terminal Type:
Solder well single mating end all contact groupings
Insert Material Specification:
Mil-m-14, ty sdg-f military specification single material response single mating end
Included Contact Quantity:

**Included Contact Type:** 

Round socket single mating end 2nd contact grouping

3 single mating end 2nd contact grouping

## NSN 5935-01-233-8170

Electrical Receptacle Connector - Page 2 of 2



## Special Features: Socket contacts located in positions b, c and d Precious Material And Location: Contact surfaces gold Precious Material And Weight: 0.020 gold grains, troy Precious Material: Gold Shelf Life: N/a Unit Of Measure: -Demilitarization: No Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.