
NSN 5935-01-234-1970

Tip Jack - Page 1 of 2





Thread Class: 2a **Thread Direction: Right-hand Electrical Insulation Feature:** Insulated from panel **Identification Code Color:** White **Body Style:** Threaded bushing mounted **Overall Length:** 0.906 inches Mounting Bushing Length: 0.469 inches **Body Length:** 0.656 inches **Overall Diameter:** 0.438 inches **Bushing Accommodation Hole Shape:** Round Maximum Voltage Rating In Volts: 1000.0 ac Accommodated Finger Type: Banana spring single finger **Finger Accommodation Diameter:** 0.161 inches single finger **Bushing Thru-hole Accommodation Diameter:** 0.312 inches **Capacitance In Picofarads:** 5.0 **End Application:** 4920-01-180-9699 adapter, test **Thread Length:** 0.469 inches **Current Rating In Amps:** 15.0 Mounting Facility Type And Quantity: 1 bushing Thready Qty Per Inch (tpi): 32 **Thread Size:** 0.312 inches

NSN 5935-01-234-1970

Tip Jack - Page 2 of 2

Terminal Type:

Turret

Material:

Plastic, polyamide body

Material:

Plastic polyamide body

Surface Treatment:

Tin contact

Surface Treatment:

Tin contact

Thread Series Designator:

Unef

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A03400

