Electrical Plug Connector - Page 1 of 2





Thread Class:

2a

**Thread Direction:** 

Right-hand

## Body Style:

Straight shape, internal coupling

### **Overall Length:**

0.766 inches

#### **Overall Diameter:**

1.156 inches

### Threaded Device Type:

Back shell

### Mating End Quantity:

1

#### **Contact Position Arrangement Style:**

14-97 single mating end

## **Contact Removability:**

Removable single mating end all contact groupings

#### Polarization Method:

Keyway or multiple keyway

## **Insert Position In Deg:**

34.0 and 100.0 and 128.0 and 228.0 and 265.0

#### Shell Type:

Solid

## Connector Locking Method:

Bayonet latch

## Thread Length:

0.219 inches

## Thready Qty Per Inch (tpi):

20

## Thread Size:

0.812 inches

## **Terminal Location:**

Back single mating end all contact groupings

## **Contact Material:**

Copper alloy single mating end all contact groupings

## **Contact Surface Treatment:**

Gold single mating end all contact groupings

## Contact Surface Treatment Specification:

Mil-g-45204 military specification single treatment response single mating end all contact groupings

## **Terminal Type:**

Crimp single mating end all contact groupings

# NSN 5935-01-234-5191

Electrical Plug Connector - Page 2 of 2



#### **Shell Material:**

Aluminum alloy

Shell Surface Treatment:

Cadmium

## Shell Surface Treatment Specification:

Qq-p-416 federal specification single treatment response

## **Included Contact Quantity:**

8 single mating end 2nd contact grouping

## Included Contact Type:

Round pin single mating end all contact groupings

#### **Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:** 

0.028 gold grains, troy

#### **Precious Material:**

Gold

#### **Test Data Document:**

81349-mil-c-38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## Thread Series Designator:

Unef

## Specification Data: 96906-ms27473 government standard Shelf Life: N/a Unit Of Measure: --Demilitarization: No Fiig:

A039b0

### Mil-std (military Standard):

Mil-g-45204 spec.