

View Online at <https://aerobasegroup.com/nsn/5935-01-234-7195>

Body Style:

Straight shape

Overall Length:

0.270 inches

Overall Height:

0.730 inches

Overall Width:

0.085 inches

Environmental Protection:

Corrosion resistant and moisture resistant and vibration resistant

Mating End Quantity:

1

Contact Position Arrangement Style:

1 row of contacts non-inserted board single mating end

Contact Removability:

Nonremovable single mating end 1st contact grouping

Contact Maximum Current Rating In Amps:

2.0 single mating end 1st contact grouping

Contact Maximum Ac Voltage Rating In Volts:

250.0 single mating end 1st contact grouping

Polarization Method:

Contact

Connector Locking Method:

Friction

End Application:

5860-01-070-3841 airborne laser tracer

Terminal Location:

Back single mating end 1st contact grouping

Contact Material:

Copper alloy single mating end 1st contact grouping

Contact Surface Treatment:

Gold single mating end 1st contact grouping and copper single mating end 1st contact grouping

Insert Material:

Plastic diallyl phthalate single mating end and glass fiber single mating end or plastic polyester single mating end

Contact Surface Treatment Specification:

Mil-g-45204, type 2 military specification 1st treatment response single mating end 1st contact grouping

Criticality Code Justification:

Feat

Insert Material Specification:

Mil-m-14, type sdg military specification 1st material response single mating end and mil-m-14, type sdg military specification 2nd material response single mating end or mil-m-24519 military specification 3rd material response single mating end

Included Contact Quantity:

4 single mating end 1st contact grouping

Special Features:

Contact omitted in position number 2

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.004 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.