

View Online at <https://aerobasegroup.com/nsn/5935-01-234-7754>

Thread Class:

2a and 2b and 2b

Thread Direction:

Right-hand and right-hand and right-hand

Body Style:

Straight shape, rectangular

Overall Length:

1.360 inches

Overall Height:

0.902 inches

Overall Width:

4.128 inches

Environmental Protection:

Thermal shock resistant and humidity resistant and vibration resistant and shock resistant and salt water resistant

Center To Center Distance Between Mounting Facilities Parallel To Height:

0.450 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

3.808 inches

Threaded Device Type:

Coupling facility and mounting hole

Mating End Quantity:

1

Contact Position Arrangement Style:

244 single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Connector Locking Method:

Jackscrew

Thready Qty Per Inch (tpi):

32 and 56 and 40

Thread Size:

0.138 inches and 0.086 inches and 0.112 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and copper single mating end single contact grouping

Insert Material:

Plastic polyester single mating end and glass fiber single mating end

Contact Surface Treatment Specification:

Mil-g-45204, type 2, cl 1, grade b or c military specification 1st treatment response single mating end single contact grouping and

mil-c-14550, cl 4 military specification 2nd treatment response single mating end single contact grouping

Terminal Type:

Pin single mating end single contact grouping

Insert Material Specification:

Mil-m-24519, ty gbt-30f military specification 1st material response single mating end and mil-p-46161, cl 3, grade b military specification 2nd material response single mating end

Included Contact Quantity:

244 single mating end single contact grouping

Included Contact Type:

Round pin single mating end single contact grouping

Special Features:

Jackscrew type-male and location-center

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.244 gold grains, troy

Precious Material:

Gold

Test Data Document:

81349-mil-c-28804 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unc and unc and unc

Specification Data:

81349-mil-c-28804/11 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.