

View Online at <https://aerobasegroup.com/nsn/5935-01-234-7867>

Body Style:

Straight shape

Overall Height:

3.110 inches

Overall Width:

2.000 inches

Unthreaded Mounting Hole Diameter:

0.120 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

2.783 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

1.437 inches

Distance From Mounting Shoulder To Front Face:

0.766 inches

Mating End Quantity:

2

Contact Position Arrangement Style:

40 all mating ends

Contact Removability:

Removable all mating ends single contact grouping

Polarization Method:

Shell and 3 polarization posts

Shell Type:

Solid

Connector Locking Method:

Friction

Terminal Location:

Back all mating ends single contact grouping

Contact Material:

Copper alloy all mating ends single contact grouping

Contact Surface Treatment:

Gold all mating ends single contact grouping and silver all mating ends single contact grouping

Insert Material:

Plastic diallyl phthalate all mating ends

Contact Surface Treatment Specification:

Mil-g-45204 military specification 1st treatment response all mating ends single contact grouping and qq-s-365 federal specification 2nd treatment response all mating ends single contact grouping

Criticality Code Justification:

Feat

Terminal Type:

Crimp all mating ends single contact grouping

Guide Design And Location:

Hexagon shape male post right-hand at 7 o'clock

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Cadmium and chromate

Included Contact Quantity:

40 1st mating end single contact grouping

Included Contact Type:

Round socket all mating ends single contact grouping

Special Features:

Includes two 4-40 threaded tabs for attaching junction shells

Precious Material And Location:

Contact surfaces gold and contact surfaces silver

Precious Material And Weight:

0.080 gold grains, troy and 0.080 silver grains, troy

Precious Material:

Gold and silver

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.