Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-234-9248

### Body Style:

Angle shape, pcb type

### Overall Length:

Between 6.390 inches and 6.410 inches

### **Overall Height:**

Between 0.540 inches and 0.560 inches

### **Overall Width:**

Between 0.480 inches and 0.500 inches

### **Environmental Protection:**

Shock resistant and vibration resistant and corrosion resistant and humidity resistant and fungus resistant

### **Unthreaded Mounting Hole Diameter:**

Between 0.110 inches and 0.130 inches

### Distance Between Mounting Facility Centers:

Between 6.140 inches and 6.160 inches

### Mating End Quantity:

1

Contact Position Arrangement Style:

160 single mating end

### Contact Removability:

Nonremovable single mating end single contact grouping

### Contact Maximum Current Rating In Amps:

5.0 single mating end single contact grouping

### Polarization Method:

Guide pin/socket

### **Connector Locking Method:**

Friction

### **Operating Tempurature Rating:**

Between -65.0 degrees celsius and 125.0 degrees celsius

### **Terminal Location:**

Back single mating end single contact grouping

### Contact Material:

Copper alloy single mating end single contact grouping

# Contact Surface Treatment:

Gold single mating end single contact grouping and nickel single mating end single contact grouping

### Insert Material:

Plastic polyphenylene single mating end

# Contact Surface Treatment Specification:

Mil-g-45204, type ii, class 1 military specification 1st treatment response single mating end single contact grouping and qq-n-290, class 2 fordered encodification 2nd treatment response single mating and single contact grouping and qq-n-290, class 2

federal specification 2nd treatment response single mating end single contact grouping

### Terminal Type:

Pin single mating end single contact grouping

# Contact Material Specification:

Qq-c-530 federal specification single material response single mating end single contact grouping

Electrical Receptacle Connector - Page 2 of 2



Guide Design And Location:
D shape socket right-hand at 9 oclock
Insert Material Specification:
Mil-m-24519 military specification single material response single mating end
Included Contact Quantity:
160 single mating end single contact grouping
Included Contact Type:
Round pin single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.0160 gold grains, troy
Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):
Mil-g-45204 spec.