NSN 5935-01-235-0439

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-235-0439

Body Style:

Straight shape, external coupling w/backshell

Overall Length:

1.925 inches

Overall Height:

1.374 inches

Overall Width:

1.374 inches

Unthreaded Mounting Hole Diameter:

Between 0.126 inches and 0.130 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

Between 1.059 inches and 1.067 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

Between 1.059 inches and 1.067 inches

Distance From Mounting Shoulder To Front Face:

Between 0.748 inches and 0.764 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

18-1 single mating end

Contact Removability:

Removable single mating end all contact groupings

Contact Maximum Current Rating In Amps:

13.0 single mating end all contact groupings

Contact Maximum Ac Voltage Rating In Volts:

500.0 single mating end 1st contact grouping

Contact Maximum Dc Voltage Rating In Volts:

700.0 single mating end 1st contact grouping

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

0.0

Shell Type:

Solid

Connector Locking Method:

Bayonet slot

Terminal Location:

Back single mating end all contact groupings

Contact Material:

Copper alloy single mating end all contact groupings

Contact Surface Treatment:

Silver single mating end all contact groupings or gold single mating end all contact groupings or rhodium single mating end all contact

groupings

NSN 5935-01-235-0439

Electrical Receptacle Connector - Page 2 of 2



Insert Material: Rubber synthetic single mating end **Contact Surface Treatment Specification:** Qq-s-365 federal specification 1st treatment response single mating end all contact groupings or mil-g-45204 military specification 2nd treatment response single mating end all contact groupings **Terminal Type:** Crimp single mating end all contact groupings Shell Material: Aluminum alloy Shell Surface Treatment: Cadmium and chromate Shell Surface Treatment Specification: Qq-p-416, type 2, cl 2 federal specification single treatment response **Included Contact Quantity:** 6 single mating end 2nd contact grouping **Included Contact Type:** Round socket single mating end all contact groupings **Precious Material And Location:** Contact surfaces silver or contact surfaces gold or contact surfaces rhodium **Precious Material And Weight:** 0.010 silver grains, troy or 0.010 gold grains, troy or 0.010 rhodium grains, troy **Precious Material:** Silver or gold or rhodium **Specification Data:** 19207-12273240 manufacturers source control Shelf Life: N/a Unit Of Measure:

Demilitarization:

No

--

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.