NSN 5935-01-235-0440

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-235-0440

Body Style: Straight shape, external coupling w/backshell **Overall Length:** 2.008 inches **Overall Height:** 1.750 inches **Overall Width:** 1.750 inches **Unthreaded Mounting Hole Diameter:** Between 0.146 inches and 0.150 inches Center To Center Distance Between Mounting Facilities Parallel To Height: Between 1.370 inches and 1.378 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: Between 1.370 inches and 1.378 inches **Distance From Mounting Shoulder To Front Face:** Between 0.811 inches and 0.827 inches **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 24-28 single mating end **Contact Removability:** Removable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 13.0 single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 200.0 single mating end single contact grouping **Contact Maximum Dc Voltage Rating In Volts:** 250.0 single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 0.0 **Shell Type:** Solid **Connector Locking Method:** Bayonet slot

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Silver single mating end single contact grouping or gold single mating end single contact grouping or rhodium single mating end single contact grouping

NSN 5935-01-235-0440

Electrical Receptacle Connector - Page 2 of 2



Insert Material:

Rubber synthetic single mating end

Contact Surface Treatment Specification:

Qq-s-365 federal specification 1st treatment response single mating end single contact grouping or mil-g-45204 military specification 2nd treatment response single mating end single contact grouping

Terminal Type:

Crimp single mating end single contact grouping

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Cadmium and chromate

Shell Surface Treatment Specification:

Qq-p-416, type 2, cl 2 federal specification all treatment responses

Included Contact Quantity:

24 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

Precious Material And Location:

Contact surfaces silver or contact surfaces gold or contact surfaces rhodium

Precious Material And Weight:

0.024 silver grains, troy or 0.024 gold grains, troy or 0.024 rhodium grains, troy

Precious Material:

Silver or gold or rhodium

Specification Data:

19207-12273240 manufacturers source control

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.