NSN 5935-01-235-2096

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-235-2096

Body Style:

Hood, side opening w/clamp

Overall Length:

4.153 inches

Overall Height:

2.358 inches

Overall Width:

0.394 inches

Environmental Protection:

Humidity resistant and vibration resistant and shock resistant

Cable Entrance Diameter:

0.787 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

2 rows of contacts non-inserted board single mating end

Contact Removability:

Removable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

3.0 single mating end single contact grouping

Polarization Method:

Guide pin/socket

Shell Type:

Hood, side opening

Connector Locking Method:

Friction

Connector Cable Strain Relief Method:

Cable clamp

Terminal Location:

Side single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold and nickel single mating end single contact grouping

Insert Material:

Glass and plastic diallyl phthalate single mating end

Contact Surface Treatment Specification:

Mil-g-45204, type 2, cl 1, grade c military specification 1st treatment response and qq-n-290, cl 2 federal specification 2nd treatment response or mil-p-27418 military specification 2nd treatment response single mating end single contact grouping

Terminal Type:

Crimp single mating end single contact grouping

Contact Material Specification:

Qq-b-626d federal specification single material response or qq-c-530 federal specification single material response or qq-b-750 federal specification single material response single mating end single contact grouping

NSN 5935-01-235-2096

Electrical Plug Connector - Page 2 of 2



Shell Material:
Steel
Shell Surface Treatment:
Passivate
Insert Material Specification:
Mil-m-14, ty sdg-f military specification all material responses single mating end
Included Contact Quantity:
65 single mating end single contact grouping
Included Contact Type:
Round socket single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.065 gold grains, troy
Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):
Mil-g-45204 spec.