Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-235-2111

## Body Style:

Right angle type

### **Overall Length:**

1.260 inches

# **Overall Height:**

1.300 inches

# **Overall Width:**

0.970 inches

### **Environmental Protection:**

Cold resistant and heat resistant

### **Unthreaded Mounting Hole Diameter:**

### 0.116 inches

Distance Between Mounting Facility Centers:

### 1.100 inches

Mating End Quantity:

1

### **Contact Position Arrangement Style:**

2 rows of contacts non-inserted board single mating end

### Contact Removability:

Removable single mating end single contact grouping

# **Contact Maximum Current Rating In Amps:**

1.0 single mating end single contact grouping

# Contact Maximum Ac Voltage Rating In Volts:

500.0 single mating end single contact grouping

### **Connector Locking Method:**

Latch

### **Terminal Location:**

Side single mating end single contact grouping

# **Contact Material:**

Copper alloy single mating end single contact grouping

### **Contact Surface Treatment:**

Gold single mating end single contact grouping

### **Insert Material:**

Plastic polyester single mating end

# Contact Surface Treatment Specification:

Mil-g-45204 military specification single treatment response single mating end single contact grouping

# **Terminal Type:**

Wire wrap single mating end single contact grouping

### Insert Material Specification:

Mil-m-24519, ty gpt-15f or gpt-20f or gpt-30f military specification single material response single mating end

# Included Contact Quantity:

10 single mating end single contact grouping



#### **Included Contact Type:**

Round pin single mating end single contact grouping

### **Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:** 

0.010 gold grains, troy

# **Precious Material:**

Gold

#### **Test Data Document:**

81349-mil-c-83503 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

#### **Specification Data:**

81349-mil-c-83503/24 government specification

Shelf Life: N/a Unit Of Measure: --Demilitarization: No Fiig: A039b0 Mil-std (military Standard):

Mil-g-45204 spec.