# NSN 5935-01-235-3207

Cadmium and chromate

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-235-3207

Pody Style
Body Style:
Straight shape
Overall Length:
1.213 inches
Overall Height:
0.648 inches
Overall Width:
0.494 inches
Unthreaded Mounting Hole Diameter:
0.154 inches
Distance Between Mounting Facility Centers:
0.984 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
9 single mating end
Contact Removability:
Removable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
5.0 single mating end single contact grouping
Polarization Method:
Mating end
Shell Type:
Solid
End Application:
4920-01-180-7543 adapter, test
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and nickel single mating end single contact grouping
Insert Material:
Plastic diallyl phthalate single mating end
Contact Surface Treatment Specification:
Mil-g-45204 military specification 1st treatment response single mating end single contact grouping
Terminal Type:
Crimp single mating end single contact grouping
Shell Material:
Steel
Shell Surface Treatment:

# NSN 5935-01-235-3207

Electrical Receptacle Connector - Page 2 of 2



#### **Shell Surface Treatment Specification:**

Qq-p-416 federal specification all treatment responses

## **Insert Material Specification:**

Mil-m-14, ty sgd-f military specification single material response single mating end

## **Included Contact Quantity:**

9 single mating end single contact grouping

## **Included Contact Type:**

Round socket single mating end single contact grouping

#### **Precious Material And Location:**

Contact surfaces gold

#### **Precious Material And Weight:**

0.009 gold grains, troy

**Precious Material:** 

Gold

Shelf Life:

N/a

**Unit Of Measure:** 

--

**Demilitarization:** 

No

Fiig:

A039b0

# Mil-std (military Standard):

Mil-g-45204 spec.