

NSN 5935-01-235-6582 Electrical Receptacle Connector - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5935-01-235-6582 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 1.050 inches **Overall Diameter:** 0.515 inches **Environmental Protection:** Corrosion resistant and moisture resistant and shock resistant and vibration resistant **Mounting Facility Thickness:** Between 0.046 inches and 0.125 inches **Threaded Device Type:** Mounting bushing **Mating End Quantity:** 1 **Contact Position Arrangement Style:** Bnc single mating end **Contact Removability:** Nonremovable single mating end single contact grouping Shell Type: Solid **Connector Locking Method:** Bayonet pin Thready Qty Per Inch (tpi): 32 Thread Size:

0.375 inches

**Terminal Location:** 

Back single mating end single contact grouping

**Contact Material:** 

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:** 

Tin single mating end single contact grouping

**Insert Material:** 

Plastic single mating end and glass single mating end

**Terminal Type:** 

Solder well single mating end single contact grouping

**Shell Material:** 

Copper alloy

## NSN 5935-01-235-6582

Electrical Receptacle Connector - Page 2 of 2



Shell Surface Treatment:
Nickel
Included Contact Quantity:
1 single mating end single contact grouping
Bushing Accommodation Hole Shape:
Round w/flat
Included Contact Type:
Coaxial socket single mating end single contact grouping
Special Features:
Grounding lug
Thread Series Designator:
Unef
Shelf Life:
N/a
Unit Of Measure:
<del>.</del>
Demilitarization:
No
Fiig:
A039b0