NSN 5935-01-235-9545

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-235-9545 **Body Style:** Straight shape, external coupling **Overall Length:** 0.697 inches **Overall Height:** 1.703 inches **Overall Width:** 1.703 inches **Unthreaded Mounting Hole Diameter:** Between 0.142 inches and 0.157 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 1.375 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.375 inches **Distance From Mounting Shoulder To Front Face:** Between 0.442 inches and 0.447 inches **Mating End Quantity:** 1 **Contact Removability:** Removable single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 334.0 Shell Type: Solid **Connector Locking Method:** Bayonet pin **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping **Contact Surface Treatment Specification:** Mil-g-45204 military specification single treatment response single mating end single contact grouping **Terminal Type:** Crimp single mating end single contact grouping **Shell Material:** Aluminum alloy **Shell Surface Treatment:**

Cadmium

NSN 5935-01-235-9545

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.

Electrical Receptacle Connector - Page 2 of 2



Shell Surface Treatment Specification:
Qq-p-416 federal specification single treatment response
Included Contact Quantity:
29 single mating end single contact grouping
Included Contact Type:
Round socket single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.029 gold grains, troy
Precious Material:
Gold
Test Data Document:
81349-mil-c-38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Data:
96906-ms27508 government standard
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
No
Fiia: