

View Online at <https://aerobasegroup.com/nsn/5935-01-236-0270>

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

32-79 all mating ends

**Contact Removability:**

Nonremovable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:**

1.5 single mating end single contact grouping

**Radio Frequency Type Contact Characteristic Impedance In Ohms:**

50.0 single mating end single contact grouping

**Contact Material:**

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping and copper single mating end single contact grouping

**Contact Surface Treatment Specification:**

Mil-g-45204, type 11, class 2 military specification 1st treatment response single mating end single contact grouping and mil-c-14550, class 4 federal specification 2nd treatment response single mating end single contact grouping

**Terminal Type:**

Pin single mating end single contact grouping

**Contact Material Specification:**

Qq-b-626, comp 22, 1/2 hard temper federal specification single material response single mating end single contact grouping

**Included Contact Quantity:**

5 single mating end single contact grouping

**Special Features:**

0.448 in. Lg.; 0.312 in. W.; 0.312 in. High; terminal lg.=0.155 in.; terminal w.=0.040 in.; terminal height=0.020 in.

**Precious Material And Location:**

Terminals gold

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0

**Mil-std (military Standard):**

Mil-g-45204 spec.