

View Online at <https://aerobasegroup.com/nsn/5935-01-236-0270>

Mating End Quantity:

1

Contact Position Arrangement Style:

32-79 all mating ends

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

1.5 single mating end single contact grouping

Radio Frequency Type Contact Characteristic Impedance In Ohms:

50.0 single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and copper single mating end single contact grouping

Contact Surface Treatment Specification:

Mil-g-45204, type 11, class 2 military specification 1st treatment response single mating end single contact grouping and mil-c-14550, class 4 federal specification 2nd treatment response single mating end single contact grouping

Terminal Type:

Pin single mating end single contact grouping

Contact Material Specification:

Qq-b-626, comp 22, 1/2 hard temper federal specification single material response single mating end single contact grouping

Included Contact Quantity:

5 single mating end single contact grouping

Special Features:

0.448 in. Lg.; 0.312 in. W.; 0.312 in. High; terminal lg.=0.155 in.; terminal w.=0.040 in.; terminal height=0.020 in.

Precious Material And Location:

Terminals gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.