Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-236-4194

Thread Class:

2a and 2b and 2a

Thread Direction:

Right-hand and right-hand

Body Style:

Straight shape

Overall Length:

3.850 inches

Overall Height:

0.732 inches

Overall Width:

0.250 inches

Environmental Protection:

Salt water resistant and humidity resistant and shock resistant and vibration resistant

Distance Between Mounting Facility Centers:

3.650 inches

Threaded Device Type:

Coupling facility and mounting stud

Mating End Quantity:

1

Contact Position Arrangement Style:

2 rows of contacts non-inserted board single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

5.0 single mating end single contact grouping

Polarization Method:

Jackscrew

Connector Locking Method:

Jackscrew-socket

Thready Qty Per Inch (tpi):

56 and 56

Thread Size:

0.086 inches and 0.086 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Plastic polyphenylene single mating end

Electrical Receptacle Connector - Page 2 of 2



Contact Surface Treatment Specification: Mil-g-45204 military specification single treatment response single mating end single contact grouping **Criticality Code Justification:** Feat **Terminal Type:** Pin single mating end single contact grouping **Contact Material Specification:** Qq-c-530 federal specification single material response single mating end single contact grouping **Insert Material Specification:** Mil-m-24519 military specification single material response single mating end **Unable To Decode:** Unable to decode and unable to decode **Included Contact Quantity:** 69 single mating end single contact grouping **Included Contact Type:** Round pin single mating end single contact grouping **Special Features:** Polarizing pin inserted in pin position six **Precious Material And Location:** Contact surfaces gold **Precious Material And Weight:** 0.069 gold grains, troy **Precious Material:** Gold **Thread Series Designator:** Unc and unc Shelf Life: N/a Unit Of Measure: --**Demilitarization:** No Fiig: A039b0 Mil-std (military Standard): Mil-g-45204 spec.