NSN 5935-01-236-8811

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-236-8811

| Thread Class: |
|--|
| 2a and 2b |
| Thread Direction: |
| Right-hand |
| Body Style: |
| Straight shape w/screw locks |
| Overall Length: |
| 1.350 inches |
| Overall Height: |
| Between 0.475 inches and 0.495 inches |
| Overall Width: |
| 0.250 inches |
| Threaded Device Type: |
| Coupling facility |
| Mating End Quantity: |
| 1 |
| Contact Position Arrangement Style: |
| 2 rows of contacts non-inserted board single mating end |
| Contact Removability: |
| Nonremovable single mating end single contact grouping |
| Polarization Method: |
| Jackscrew |
| Connector Locking Method: |
| Jackscrew-socket |
| Thready Qty Per Inch (tpi): |
| 56 |
| Thread Size: |
| 0.086 inches |
| Terminal Location: |
| Back single mating end single contact grouping |
| Contact Material: |
| Copper alloy single mating end single contact grouping |
| Contact Surface Treatment: |
| Gold single mating end single contact grouping |
| Insert Material: |
| Plastic polyphenylene single mating end and glass fiber single mating end |
| Contact Surface Treatment Specification: |
| Mil-g-45204 military specification single treatment response single mating end single contact grouping |
| Terminal Type: |
| Solder well single mating end single contact grouping |
| Insert Material Specification: |
| Mil p 46174 of 40 grade a military energication all material responses single mating and |

NSN 5935-01-236-8811

Electrical Plug Connector - Page 2 of 2



Included Contact Quantity: 20 single mating end single contact grouping **Included Contact Type:** Round pin single mating end single contact grouping **Precious Material And Location:** Contact surfaces gold **Precious Material And Weight:** 0.020 gold grains, troy **Precious Material:** Gold **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure:** Demilitarization: No Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.