NSN 5935-01-236-8817

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-236-8817

Body Style:

Right angle type

Overall Length:

3.550 inches

Body Height:

0.325 inches

Environmental Protection:

Corrosion resistant and humidity resistant and moisture proof and shock resistant and vibration resistant

Unthreaded Mounting Hole Diameter:

0.070 inches

Distance Between Mounting Facility Centers:

3.330 inches

Mating End Quantity:

4

Contact Position Arrangement Style:

2 rows of contacts non-inserted board single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

3.0 single mating end single contact grouping

Connector Locking Method:

Friction

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and nickel single mating end single contact grouping

Insert Material:

Glass fiber single mating end and plastic phenolic single mating end

Terminal Type:

Solder well single mating end single contact grouping

Insert Material Specification:

Mil-m-14, ty mfh military specification all material responses single mating end

Included Contact Quantity:

60 single mating end single contact grouping

Included Contact Type:

Round pin single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.060 gold grains, troy

NSN 5935-01-236-8817

Electrical Receptacle Connector - Page 2 of 2



Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Demilitarization:
No

Mil-std (military Standard):

Mil-m-14 spec.