Electrical Plug Connector Body - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-236-8831

| Thread Class: |
|--|
| 2a |
| Thread Direction: |
| Right-hand |
| Body Style: |
| Straight shape, internal coupling |
| Overall Length: |
| 0.766 inches |
| Overall Diameter: |
| 1.281 inches |
| Threaded Device Type: |
| Back shell |
| Mating End Quantity: |
| 1 |
| Contact Position Arrangement Style: |
| 16-35 single mating end |
| Polarization Method: |
| Keyway or multiple keyway |
| Insert Position In Deg: |
| 0.0 |
| Shell Type: |
| Solid |
| Connector Locking Method: |
| Bayonet latch |
| Thread Length: |
| 0.219 inches |
| Thready Qty Per Inch (tpi): |
| 20 |
| Thread Size: |
| 0.938 inches |
| Shell Material: |
| Aluminum alloy |
| Shell Surface Treatment: |
| Cadmium |
| Shell Surface Treatment Specification: |
| Qq-p-416 federal specification single treatment response |
| Test Data Document: |
| Mil-dtl-38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; |

excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unef



Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-dtl-38999 spec.