# NSN 5935-01-237-9945



Electrical Receptacle Connector - Page 1 of 3 View Online at https://aerobasegroup.com/nsn/5935-01-237-9945 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 1.405 inches **Overall Height:** 1.532 inches **Overall Width:** 1.532 inches **Environmental Protection:** Moisture proof and salt water resistant and vibration proof **Unthreaded Mounting Hole Diameter:** 0.150 inches **Center To Center Distance Between Mounting Facilities Parallel To Height:** 1.203 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.203 inches **Distance From Mounting Shoulder To Front Face:** Between 0.462 inches and 0.493 inches **Threaded Device Type:** Back shell **Mating End Quantity: Contact Position Arrangement Style:** 18-8 single mating end **Contact Removability:** Removable single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 600.0 single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 180.0 Shell Type: Solid **Connector Locking Method:** Bayonet pin

Thread Length: 0.290 inches

# NSN 5935-01-237-9945

Electrical Receptacle Connector - Page 2 of 3



# Thready Qty Per Inch (tpi):

18

#### **Thread Size:**

1.062 inches

#### **Terminal Location:**

Back single mating end single contact grouping

#### **Contact Surface Treatment:**

Gold single mating end single contact grouping and nickel single mating end single contact grouping

#### **Contact Surface Treatment Specification:**

Mil-g-45204, type 1, cl 1, grade c military specification 1st treatment response single mating end single contact grouping and qq-n-290, grade e federal specification 2nd treatment response single mating end single contact grouping

#### **Terminal Type:**

Crimp single mating end single contact grouping

# **Shell Material:**

Aluminum alloy 6061

#### **Shell Surface Treatment:**

Cadmium

#### **Shell Surface Treatment Specification:**

Qq-p-416 federal specification single treatment response

#### **Shell Material Specification:**

Qq-a-591, a380 federal specification single material response or qq-a-367, t6 federal specification single material response

# **Included Contact Quantity:**

8 single mating end single contact grouping

#### **Included Contact Type:**

Round pin single mating end single contact grouping

#### **Special Features:**

In order to complete the connector assembly, the user must obtain/provide the backshell. Standard versions may be ordered as nsn 5935-01-177-9556, p/n m85049/52-1-18w for the straight style, or nsn 5935-01-174-3671, p/n m85049/51-1-18w for the right angle style.

# **Precious Material And Location:**

Contact surfaces gold

#### **Precious Material And Weight:**

0.008 gold grains, troy

#### **Precious Material:**

Gold

# Test Data Document:

81349-mil-c-26482 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

# **Thread Series Designator:**

Unef

#### **Specification Data:**

96906-ms3472 government standard

#### Shelf Life:

N/a

#### **Unit Of Measure:**

# NSN 5935-01-237-9945

Electrical Receptacle Connector - Page 3 of 3



Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.