NSN 5935-01-238-2192

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-238-2192

Body Style:
Straight type
Overall Length:
3.095 inches
Overall Height:
1.260 inches
Overall Width:
0.590 inches
Environmental Protection:
Heat resistant and cold resistant
Unthreaded Mounting Hole Diameter:
Between 0.122 inches and 0.127 inches
Distance Between Mounting Facility Centers:
2.775 inches
Mating End Quantity:
1
Contact Removability:
Removable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
5.0 single mating end single contact grouping
Polarization Method:
Mating end
Connector Locking Method:
Friction
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping
Insert Material:
Plastic diallyl phthalate single mating end
Contact Surface Treatment Specification:
Mil-g-45204 military specification single treatment response single mating end single contact grouping
Terminal Type:
Crimp single mating end single contact grouping
Contact Material Specification:
Qq-c-530 federal specification single material response single mating end single contact grouping
Insert Material Specification:
Mil-p-46137 military specification single material response single mating end
Included Contact Quantity:

moradea contact quantity.

72 single mating end single contact grouping

NSN 5935-01-238-2192

Electrical Receptacle Connector - Page 2 of 2



Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.072 gold grains, troy
Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0

Mil-std (military Standard):

Mil-g-45204 spec.