Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-238-8581

Body Style:	
Right angle type	
Overall Length:	
1.213 inches	
Body Height:	
0.494 inches	
Environmental Protection:	
Corrosion resistant and humidity resistant and shock resistant and vibration resistant	
Unthreaded Mounting Hole Diameter:	
0.120 inches	
Distance Between Mounting Facility Centers:	
0.984 inches	
Mating End Quantity:	
1	
Contact Position Arrangement Style:	
9 single mating end	
Contact Removability:	
Nonremovable single mating end single contact grouping	
Polarization Method:	
Mating end	
Shell Type:	
Solid	
Connector Locking Method:	
Friction	
End Application:	
Receiving set, radio remote an/arw-8 (v) 5	
Terminal Location:	
Side single mating end single contact grouping	
Contact Material:	
Copper alloy single mating end single contact grouping	
Contact Surface Treatment:	
Gold single mating end single contact grouping	
Insert Material:	
Plastic diallyl phthalate single mating end	
Contact Surface Treatment Specification:	
Mil-g-45204, type 2, gr c, cl 1 military specification single treatment response single mating end single contact grouping	J
Terminal Type:	
Pin single mating end single contact grouping	
Shell Material:	
Metal	
Shell Surface Treatment:	
Cadmium	



Shell Surface Treatment Specification: Qq-p-416 federal specification single treatment response **Insert Material Specification:** Mil-m-14, ty sdg-f military specification single material response single mating end or mil-m-24519, ty gpt-30f or ty get-30f military specification single material response single mating end **Included Contact Quantity:** 9 single mating end single contact grouping Included Contact Type: Round socket single mating end single contact grouping **Special Features:** Furnished items - bracket **Precious Material And Location:** Contact surfaces gold **Precious Material And Weight:** 0.009 gold grains, troy **Precious Material:** Gold Shelf Life: N/a Unit Of Measure: ---Demilitarization: No Fiig: A039b0 Mil-std (military Standard): Mil-g-45204 spec.