Electrical Plug Connector - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5935-01-239-1770



#### **Thread Class:**

2a and 2b

**Thread Direction:** 

Right-hand

# Body Style:

Straight shape w/screw locks

#### **Overall Length:**

0.870 inches

#### **Overall Height:**

0.920 inches

#### **Overall Width:**

0.190 inches

# Threaded Device Type:

Coupling facility

#### Mating End Quantity:

1

# Contact Position Arrangement Style:

9 single mating end

#### **Contact Removability:**

Removable single mating end single contact grouping

#### **Contact Maximum Current Rating In Amps:**

3.0 single mating end single contact grouping

# **Polarization Method:**

Jackscrew

#### **Connector Locking Method:**

Jackscrew

#### Thready Qty Per Inch (tpi):

56

# Thread Size:

0.086 inches

#### **Terminal Location:**

Back single mating end single contact grouping

#### **Contact Material:**

Copper alloy single mating end single contact grouping

#### **Contact Surface Treatment:**

Gold single mating end single contact grouping

## **Insert Material:**

Plastic diallyl phthalate single mating end

# **Contact Surface Treatment Specification:**

Mil-g-45204 military specification single treatment response single mating end single contact grouping

## **Terminal Type:**

Crimp single mating end single contact grouping

# NSN 5935-01-239-1770

Electrical Plug Connector - Page 2 of 2



**Insert Material Specification:** Mil-p-19833, ty gdi-30f military specification single material response single mating end **Included Contact Quantity:** 9 single mating end single contact grouping Included Contact Type: Round socket single mating end single contact grouping **Precious Material And Location:** Contact surfaces gold **Precious Material And Weight:** 0.009 gold grains, troy **Precious Material:** Gold **Thread Series Designator:** Unc Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A039b0 Mil-std (military Standard): Mil-g-45204 spec.