Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-239-2054

Thread Class:
2a
Thread Direction:
Right-hand
Body Style:
Straight shape, internal coupling
Overall Length:
0.766 inches
Overall Diameter:
1.031 inches
Threaded Device Type:
Back shell
Mating End Quantity:
1
Contact Position Arrangement Style:
13119 single mating end
Contact Removability:
Removable single mating end single contact grouping
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
100.0 and 128.0 and 228.0 and 265.0 and 328.0
Shell Type:
Solid
Connector Locking Method:
Bayonet latch
Thread Length:
0.219 inches
Thready Qty Per Inch (tpi):
24
Thread Size:
0.688 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping
Contact Surface Treatment Specification:
Mil-g-45204 military specification single treatment response single mating end single contact grouping
Terminal Type:

Crimp single mating end single contact grouping

# NSN 5935-01-239-2054

Electrical Plug Connector - Page 2 of 2



#### **Shell Material:**

Aluminum alloy

#### Shell Surface Treatment:

Cadmium

# Shell Surface Treatment Specification:

Qq-p-416 federal specification single treatment response

### **Included Contact Quantity:**

22 single mating end single contact grouping

## Included Contact Type:

Round pin single mating end single contact grouping

#### **Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:** 

0.022 gold grains, troy

#### **Precious Material:**

Gold

#### **Test Data Document:**

81349-mil-c-38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

# Thread Series Designator:

Unef

# Specification Data: 96906-ms27473 government standard Shelf Life: N/a Unit Of Measure: --Demilitarization: No Fiig:

A039b0

#### Mil-std (military Standard):

Mil-g-45204 spec.