

View Online at <https://aerobasegroup.com/nsn/5935-01-239-2063>

**Overall Length:**

1.328 inches

**Overall Diameter:**

1.183 inches

**Environmental Protection:**

Moisture proof and salt water resistant and vibration proof

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

14-15 single mating end

**Contact Removability:**

Nonremovable single mating end all contact groupings

**Contact Maximum Ac Voltage Rating In Volts:**

600.0 single mating end all contact groupings

**Polarization Method:**

Keyway or multiple keyway

**Insert Position In Deg:**

0.0

**Shell Type:**

Solid

**Connector Locking Method:**

Bayonet latch

**End Application:**

6625-01-190-9570 radiac set

**Contact Surface Treatment:**

Gold single mating end all contact groupings and nickel single mating end all contact groupings

**Contact Surface Treatment Specification:**

Mil-g-45204, type 1, cl 1, grade c military specification 1st treatment response single mating end all contact groupings and qq-n-290, grade e federal specification 2nd treatment response single mating end all contact groupings

**Shell Material:**

Aluminum alloy

**Shell Surface Treatment:**

Cadmium and chromate

**Shell Surface Treatment Specification:**

Qq-p-416, type 2, cl 3 federal specification all treatment responses

**Shell Material Specification:**

Qq-a-591 federal specification single material response

**Included Contact Quantity:**

14 single mating end 2nd contact grouping

**Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:**

0.015 gold grains, troy

**Precious Material:**

Gold

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0

**Mil-std (military Standard):**

Mil-g-45204 spec.