## NSN 5935-01-239-4999

Electrical Receptacle Connector Body - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-239-4999 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 1.300 inches **Overall Height:** 1.125 inches **Overall Width:** 1.125 inches **Unthreaded Mounting Hole Diameter:** 0.120 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 0.906 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 0.906 inches **Distance From Mounting Shoulder To Front Face:** Between 0.708 inches and 0.728 inches **Threaded Device Type:** Back shell **Mating End Quantity: Contact Position Arrangement Style:** 14-12 single mating end **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 18.0 and 149.0 and 192.0 and 259.0 Shell Type: **Connector Locking Method:** Bayonet pin Thready Qty Per Inch (tpi): 20 **Thread Size:** 0.875 inches **Insert Material:** Plastic phenolic mineral filled single mating end

**Shell Material:** Aluminum alloy

## NSN 5935-01-239-4999

Electrical Receptacle Connector Body - Page 2 of 2



Shell Surface Treatment:
Cadmium and chromate
Shell Surface Treatment Specification:
Qq-p-416, type 2, cl 3 federal specification all treatment responses
Shell Material Specification:
Qq-a-367 federal specification single material response
Insert Material Specification:
Mil-m-14, ty mfh military specification single material response single mating end
Thread Series Designator:
Unef
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

Mil-std (military Standard): Mil-m-14 spec.

No Fiig: A039b0