AeroBase Group

View Online at https://aerobasegroup.com/nsn/5935-01-239-7380

Body Style:

Straight type

Overall Length:

2.350 inches

Overall Width:

0.250 inches

Body Height:

0.335 inches

Environmental Protection:

Corrosion resistant and cold resistant and heat resistant and humidity resistant and vibration resistant

Mating End Quantity:

1

Contact Position Arrangement Style:

2 rows of contacts non-inserted board single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

5.0 single mating end single contact grouping

Polarization Method:

Guide pin/socket

Connector Locking Method:

Friction

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and nickel single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate single mating end and glass fiber single mating end or plastic polyphenylene single mating end

Contact Surface Treatment Specification:

Mil-g-45204, type 2, gr c, cl 1 military specification 1st treatment response single mating end single contact grouping

Terminal Type:

Pin single mating end single contact grouping

Contact Material Specification:

Qq-c-530 federal specification single material response single mating end single contact grouping

Insert Material Specification:

Mil-m-14f, type sdgf military specification all material responses single mating end or mil-p-46174 military specification single material

response single mating end

Unable To Decode:

Unable to decode and unable to decode

Included Contact Quantity:

40 single mating end single contact grouping



Included Contact Type: Round socket single mating end single contact grouping Precious Material And Location: Contact surfaces gold Precious Material And Weight: 0.040 gold grains, troy Precious Material: Gold Shelf Life: N/a Unit Of Measure: --Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.