

View Online at <https://aerobasegroup.com/nsn/5935-01-239-7728>

Thread Class:

2a and 2b

Thread Direction:

Right-hand

Body Style:

Straight shape

Overall Length:

1.312 inches

Overall Height:

1.831 inches

Overall Width:

0.375 inches

Environmental Protection:

Humidity resistant and shock resistant and thermal shock resistant and vibration resistant

Threaded Device Type:

Coupling facility

Mating End Quantity:

1

Contact Position Arrangement Style:

9 single mating end

Contact Removability:

Removable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

7.5 single mating end single contact grouping

Polarization Method:

Jackscrew

Connector Locking Method:

Jackscrew-socket

End Application:

1430-01-087-6338 engage control

Thread Length:

0.320 inches

Thread Qty Per Inch (tpi):

32

Thread Size:

0.138 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate single mating end and glass fiber single mating end

Contact Surface Treatment Specification:

Mil-g-45204, type 2, grade c, class 1 military specification single treatment response single mating end single contact grouping

Terminal Type:

Crimp single mating end single contact grouping

Contact Material Specification:

Qq-c-530 federal specification single material response single mating end single contact grouping or qq-c-533 federal specification single material response single mating end single contact grouping

Insert Material Specification:

Mil-m-14, ty sdg-f military specification all material responses single mating end or mil-p-19833, ty gdi-3of military specification all material responses single mating end

Included Contact Quantity:

9 single mating end single contact grouping

Included Contact Type:

Round pin single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.009 gold grains, troy

Precious Material:

Gold

Test Data Document:

81349-mil-c-28748 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unc

Specification Data:

81349-mil-c-28748/3 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.