# NSN 5935-01-239-8898

Electrical Receptacle Connector Body - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-239-8898

view Offiline at https://defobasegroup.com/hsh/0900-01-209-0000
Thread Class:
2a and 2a and 2b
Thread Direction:
Right-hand and right-hand
Body Style:
Straight shape, external coupling
Overall Length:
33.66 millimeters
Overall Height:
39.7 millimeters
Overall Width:
39.7 millimeters
Center To Center Distance Between Mounting Facilities Parallel To Height:
Between 29.36 millimeters and 31.75 millimeters
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
Between 29.36 millimeters and 31.75 millimeters
Distance From Mounting Shoulder To Front Face:
20.1 millimeters
Threaded Device Type:
Back shell and coupling facility and hub
Mating End Quantity:
12
Contact Position Arrangement Style:
21-35 single mating end
Polarization Method:
Keyway or multiple keyway and key, multiple key groove
Insert Position In Deg:
342.0
Shell Type:
Solid
Connector Locking Method:
Externally threaded shell
Thready Qty Per Inch (tpi):
10 and 32 and 18
Thread Size:
31.0 millimeters and 1.375 inches
Thread Pitch In Millimeters:
1.00 and 1.00
Shell Material:
Aluminum alloy or zinc

Cadmium and chromate and zinc

**Shell Surface Treatment:** 

# NSN 5935-01-239-8898

Electrical Receptacle Connector Body - Page 2 of 2



#### **Shell Surface Treatment Specification:**

Qq-p-416 ty ii, cl 3 federal specification single treatment response

#### **Thread Tolerance Class:**

6g external and 6h external

## **Test Data Document:**

81349-dod-c-38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## **Thread Series Designator:**

Iso m and special acme

#### **Specification Data:**

81349-dod-c-38999/20 government specification

Shelf Life:

N/a

**Unit Of Measure:** 

--

**Demilitarization:** 

No

Fiig:

A039b0