Electrical Plug Connector - Page 1 of 2

AeroBase Group

View Online at https://aerobasegroup.com/nsn/5935-01-240-2275

Thread Class: 2b Thread Direction: Right-hand Body Style: Straight shape, internal coupling w/strain relief Body Length: 3.442 inches Overall Diameter: 1.250 inches Environmental Protection:
Thread Direction: Right-hand Body Style: Straight shape, internal coupling w/strain relief Body Length: 3.442 inches Overall Diameter: 1.250 inches
Right-hand Body Style: Straight shape, internal coupling w/strain relief Body Length: 3.442 inches Overall Diameter: 1.250 inches
Body Style: Straight shape, internal coupling w/strain relief Body Length: 3.442 inches Overall Diameter: 1.250 inches
Straight shape, internal coupling w/strain relief Body Length: 3.442 inches Overall Diameter: 1.250 inches
Body Length: 3.442 inches Overall Diameter: 1.250 inches
3.442 inches Overall Diameter: 1.250 inches
Overall Diameter: 1.250 inches
1.250 inches
Environmental Protection:
Moisture proof and vibration proof and salt water resistant
Cable Entrance Diameter:
Between 0.316 inches and 0.531 inches
Threaded Device Type:
Coupling facility
Mating End Quantity:
1
Contact Position Arrangement Style:
16-10 single mating end
Contact Removability:
Removable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
13.0 single mating end single contact grouping
Contact Maximum Ac Voltage Rating In Volts:
500.0 single mating end single contact grouping
Contact Maximum Dc Voltage Rating In Volts:
700.0 single mating end single contact grouping
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
90.0
Shell Type:
Solid
Connector Locking Method:
Internally threaded coupling ring
Connector Cable Strain Relief Method:
Cable clamp
Thready Qty Per Inch (tpi):
20
Thread Size:
1.000 inches

## NSN 5935-01-240-2275

Electrical Plug Connector - Page 2 of 2



**Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping and nickel single mating end single contact grouping **Insert Material:** Rubber single mating end **Terminal Type:** Crimp single mating end single contact grouping Shell Material: Aluminum alloy **Shell Surface Treatment:** Cadmium and chromate Shell Surface Treatment Specification: Qq-p-416, type 2, class 3 federal specification all treatment responses **Included Contact Quantity:** 3 single mating end single contact grouping **Included Contact Type:** Round socket single mating end single contact grouping **Precious Material And Location:** Contact surfaces gold **Precious Material And Weight:** 0.003 gold grains, troy **Precious Material:** Gold **Thread Series Designator:** Unef Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A039b0