Electrical Receptacle Connector - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5935-01-240-4141

Thread Class:

2a and 2a

Thread Direction:

Right-hand and right-hand

Body Style:

Straight shape, external coupling

Overall Length:

1.430 inches

Overall Height:

1.250 inches

Overall Width:

1.250 inches

Environmental Protection:

Humidity resistant and salt water resistant and shock proof and vibration proof

Unthreaded Mounting Hole Diameter:

Between 0.116 inches and 0.125 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

0.969 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

0.969 inches

Distance From Mounting Shoulder To Front Face:

Between 0.708 inches and 0.728 inches

Threaded Device Type:

Back shell and coupling facility

Mating End Quantity:

1

Contact Position Arrangement Style:

24 number 20 single mating end

Contact Removability:

Removable single mating end single contact grouping

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

0.0

Shell Type:

Solid

Connector Locking Method:

Externally threaded shell

Thready Qty Per Inch (tpi):

20 and 18

Thread Size:

1.000 inches and 1.062 inches

NSN 5935-01-240-4141

Electrical Receptacle Connector - Page 2 of 3



Те	rminal Location:
Ba	ck single mating end single contact grouping
	ontact Material:
Co	opper alloy single mating end single contact grouping
	ontact Surface Treatment:
Go	old single mating end single contact grouping
In	sert Material:
Pla	astic epoxy single mating end
Co	ontact Surface Treatment Specification:
Mi	l-g-45204, type 1, cl 2 military specification single treatment response single mating end single contact grouping
Те	rminal Type:
Cr	imp single mating end single contact grouping
Sł	ell Material:
Al	uminum alloy
Sł	ell Surface Treatment:
Са	ldmium
Sł	ell Surface Treatment Specification:
Q	p
Sł	ell Material Specification:
Q	a-a-367 federal specification single material response
In	cluded Contact Quantity:
24	single mating end single contact grouping
In	cluded Contact Type:
Ro	ound pin single mating end single contact grouping
Sp	ecial Features:
16	-24 insert configuration
Pr	ecious Material And Location:
Сс	ontact surfaces gold
Pr	ecious Material And Weight:
0.0	024 gold grains, troy
Pr	ecious Material:
Go	old
Те	st Data Document:
81	349-mil-c-83723 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
fo	mat; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
en	vironmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Th	read Series Designator:
Ur	nef and unef
Sp	ecification Data:
81	349-mil-c-83723/83 government specification
Sł	elf Life:
N/	a
Ur	nit Of Measure:
De	militarization:

NSN 5935-01-240-4141

Electrical Receptacle Connector - Page 3 of 3



Fiig: A039b0

Mil-std (military Standard):

Mil-g-45204 spec.