NSN 5935-01-240-7449

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-240-7449 **Thread Class:** 2a and 2b **Thread Direction:** Right-hand **Body Style:** Hood, top opening w/clamp **Overall Length:** 1.250 inches **Overall Height:** 1.844 inches **Overall Width:** 0.500 inches **Environmental Protection:** Moisture resistant and shock resistant and vibration resistant **Threaded Device Type:** Coupling facility **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 14 single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 7.5 single mating end single contact grouping **Polarization Method:** Jackscrew Shell Type: Hood, top opening **Connector Locking Method:** Jackscrew-socket **Connector Cable Strain Relief Method:** Cable clamp **Cable Opening Length:** 0.594 inches **Cable Opening Width:** 0.375 inches Thready Qty Per Inch (tpi): 32 **Thread Size:**

0.138 inches

Terminal Location:

Back single mating end single contact grouping

NSN 5935-01-240-7449

Electrical Plug Connector - Page 2 of 2



| Contact Material: |
|--|
| Copper alloy single mating end single contact grouping |
| Contact Surface Treatment: |
| Gold single mating end single contact grouping |
| Insert Material: |
| Plastic melamine mineral filled single mating end |
| Terminal Type: |
| Solder well single mating end single contact grouping |
| Shell Material: |
| Aluminum |
| Shell Surface Treatment: |
| Anodize |
| Included Contact Quantity: |
| 14 single mating end single contact grouping |
| Included Contact Type: |
| Round pin single mating end single contact grouping |
| Precious Material And Location: |
| Contact surfaces gold |
| Precious Material And Weight: |
| 0.014 gold grains, troy |
| Precious Material: |
| Gold |
| Thread Series Designator: |
| Unc |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |

No Fiig: A039b0