

View Online at <https://aerobasegroup.com/nsn/5935-01-240-8081>

Body Style:

Straight type

Overall Length:

3.810 inches

Overall Height:

0.836 inches

Overall Width:

0.345 inches

Unthreaded Mounting Hole Diameter:

0.125 inches

Distance Between Mounting Facility Centers:

3.550 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

2 rows of contacts non-inserted board single mating end

Contact Removability:

Removable single mating end single contact grouping

Polarization Method:

2 polarization posts

Connector Locking Method:

Friction

End Application:

5895-01-032-4266 programmer, interrogator set

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and copper single mating end single contact grouping

Insert Material:

Plastic polyester single mating end and glass fiber single mating end

Contact Surface Treatment Specification:

Mil-g-45204, type 2, cl 1 military specification 1st treatment response single mating end single contact grouping and mil-c-14450, cl 4 military specification 2nd treatment response single mating end single contact grouping

Terminal Type:

Crimp single mating end single contact grouping

Contact Material Specification:

Qq-c-530, cond h federal specification single material response single mating end single contact grouping

Guide Design And Location:

Hexagon shape female post left-hand at 8 o'clock and hexagon shape female post right-hand at 8 o'clock

Insert Material Specification:

Mil-p-46161, grade b, class 3 military specification all material responses single mating end

Included Contact Quantity:

50 single mating end single contact grouping

Included Contact Type:

Round pin single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.050 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.