Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-241-0249

Body Style:
Right angle type
Overall Length:
6.680 inches
Overall Height:
0.745 inches
Overall Width:
0.575 inches
Unthreaded Mounting Hole Diameter:
Between 0.096 inches and 0.101 inches
Distance Between Mounting Facility Centers:
6.350 inches
Mating End Quantity:
1
Contact Removability:
Removable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
5.0 single mating end single contact grouping
Contact Maximum Ac Voltage Rating In Volts:
1300.0 single mating end single contact grouping
Polarization Method:
Inter-contact polarizing keys
Shell Type:
Solid
Terminal Location:
Front single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping
Insert Material:
Plastic acetal single mating end and glass single mating end
Contact Surface Treatment Specification:
Mil-g-45204, type ii military specification single treatment response single mating end single contact grouping
Terminal Type:
Solder stud single mating end single contact grouping
Contact Material Specification:
Qq-c-530 federal specification single material response single mating end single contact grouping
Shell Material:
Plastic and glass
Shell Material Specification:
Milp-16161 grade class 15 military specification single material response

Mil-p-46161, grade, class 15 military specification single material response

# NSN 5935-01-241-0249

Electrical Receptacle Connector - Page 2 of 2



### **Insert Material Specification:**

Mil-p-46137 military specification single material response single mating end

### **Included Contact Quantity:**

240 single mating end single contact grouping

### Included Contact Type:

Round pin single mating end single contact grouping

## Shelf Life:

N/a

Unit Of Measure:

---

#### Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.