

View Online at <https://aerobasegroup.com/nsn/5935-01-241-5921>

Body Style:

Straight shape, internal coupling w/strain relief

Mating End Quantity:

1

Contact Position Arrangement Style:

130-2-iec-18 single mating end

Contact Removability:

Nonremovable single mating end all contact groupings

Contact Maximum Current Rating In Amps:

20.0 single mating end all contact groupings

Contact Maximum Ac Voltage Rating In Volts:

125.0 single mating end all contact groupings

Contact Maximum Dc Voltage Rating In Volts:

250.0 single mating end all contact groupings

Shell Type:

Solid

Connector Locking Method:

Spring friction

Connector Cable Strain Relief Method:

Cord protector

Terminal Location:

Back single mating end all contact groupings

Contact Material:

Copper alloy single mating end all contact groupings

Insert Material:

Plastic polyamide single mating end

Terminal Type:

Solder well single mating end all contact groupings

Shell Material:

Aluminum

Included Contact Quantity:

2 single mating end 2nd contact grouping

Included Contact Type:

Flat pin single mating end 2nd contact grouping

Special Features:

Enp plug should only be used with enr receptacle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0