## NSN 5935-01-241-7639

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-241-7639

**Body Style:** 

Straight shape

**Overall Length:** 

Between 1.019 inches and 1.049 inches

**Overall Height:** 

Between 1.110 inches and 1.140 inches

**Overall Width:** 

Between 2.297 inches and 2.327 inches

**Unthreaded Mounting Hole Diameter:** 

Between 0.105 inches and 0.135 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

Between 0.745 inches and 0.755 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

Between 1.608 inches and 1.620 inches

**Distance From Mounting Shoulder To Front Face:** 

Between 0.735 inches and 0.765 inches

**Mating End Quantity:** 

1

**Contact Position Arrangement Style:** 

"106, a106" single mating end

**Contact Removability:** 

Removable single mating end single contact grouping

**Polarization Method:** 

Mating end

Shell Type:

Solid

**Connector Locking Method:** 

Friction

**Terminal Location:** 

Back single mating end single contact grouping

**Contact Surface Treatment:** 

Gold single mating end single contact grouping

**Contact Surface Treatment Specification:** 

Mil-g-45204 military specification single treatment response single mating end single contact grouping

**Terminal Type:** 

Crimp single mating end single contact grouping

**Included Contact Quantity:** 

106 single mating end single contact grouping

**Included Contact Type:** 

Round pin single mating end single contact grouping

**Precious Material And Location:** 

Contact surfaces gold

## NSN 5935-01-241-7639

Electrical Receptacle Connector - Page 2 of 2



| <b>Precious Material And Weight:</b> |
|--------------------------------------|
| 0.106 gold grains, troy              |
| Precious Material:                   |
| Gold                                 |
| Shelf Life:                          |
| N/a                                  |
| Unit Of Measure:                     |
|                                      |
| Demilitarization:                    |
| No                                   |
| Fiig:                                |
| A039b0                               |

Mil-std (military Standard):

Mil-g-45204 spec.