## NSN 5935-01-242-2735

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-242-2735

| Body Style:   |
|---|
| Right angle type  |
| Overall Length:   |
| 2.112 inches  |
| Overall Width:  |
| 0.652 inches  |
| Body Height:  |
| Between 0.410 inches and 0.415 inches   |
| Mating End Quantity:  |
| 1   |
| Contact Position Arrangement Style:   |
| 2 rows of contacts non-inserted board single mating end   |
| Contact Removability:   |
| Nonremovable single mating end single contact grouping  |
| Polarization Method:  |
| Mating end  |
| Connector Locking Method:   |
| Detent  |
| Terminal Location:  |
| Side single mating end single contact grouping  |
| Contact Material:   |
| Copper alloy single mating end single contact grouping  |
| Contact Surface Treatment:  |
| Gold single mating end single contact grouping and nickel single mating end single contact grouping |
| Insert Material:  |
| Plastic polyamide single mating end and glass fiber single mating end                               |
| Contact Surface Treatment Specification:  |
| Mil-g-45204 military specification 1st treatment response single mating end single contact grouping |
| Terminal Type:  |
| Pin single mating end single contact grouping   |
| Included Contact Quantity:  |
| 40 single mating end single contact grouping  |
| Included Contact Type:  |
| Flat pin single mating end single contact grouping  |
| Precious Material And Location:   |
| Contact surfaces gold   |
| Precious Material And Weight:   |
| 0.040 gold grains, troy   |
| Precious Material:  |
| Gold  |
| Shelf Life:   |

N/a

## NSN 5935-01-242-2735

Electrical Receptacle Connector - Page 2 of 2



| Demilitarization: |  |
|-------------------|--|
| Nο                |  |

**Unit Of Measure:** 

No

Fiig: A039b0

\_\_\_\_

Mil-std (military Standard):

Mil-g-45204 spec.