View Online at https://aerobasegroup.com/nsn/5935-01-242-2742

Electrical Receptacle Connector Body - Page 1 of 2 **Thread Class:** 2a and 2b and 2a **Thread Direction:** Right-hand and right-hand and right-hand **Body Style:** Rectangular shape **Overall Length:** 2.843 inches Center To Center Distance Between Mounting Facilities Parallel To Length: 2.281 inches **Overall Height:** 1.409 inches **Overall Width:** 1.234 inches **Environmental Protection:** Humidity resistant and shock resistant and thermal shock resistant and vibration resistant Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 0.703 inches **Threaded Device Type:** Coupling facility and mounting stud Mating End Quantity: 1 **Contact Position Arrangement Style:** 24 single mating end **Polarization Method:** Jackscrew and guide pin/socket **Connector Locking Method:** Jackscrew-socket **End Application:** Detecting ranging set, sonar an/sqs-53b Thready Qty Per Inch (tpi): 32 and 32 and 40 **Thread Size:** 0.138 inches and 0.138 inches and 0.112 inches **Insert Material:** Plastic diallyl phthalate single mating end and glass fiber single mating end **Insert Material Specification:** Mil-m-14, type gdi-30f military specification all material responses single mating end Unable To Decode: Unable to decode and unable to decode Unable To Decode: Unable to decode and unable to decode and unable to decode and unable to decode



Thread Series Designator:

Unc and unc and unc

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-m-14 spec.